CicloSport
SPORTS INFORMATION SYSTEMS

CICLOMASTER
CM 4.4A

Congratulations on your purchase!

With the **CICLOMASTER CM 4.4A** you have acquired a wireless electronic bike computer with state of the art electronics, the highest level of precision and it is weatherproof. As special features the **CM 4.4A** has an optional cadence measurement and an optional heart rate measurement (for this you need separately available accessories).

The Two in One-System: this allows you to use this cycle computer for two different bicycles and view the combined total values.

Please read this operating manual carefully.

Package content:
- CICLOMASTER CM 4.4A
- battery type CR 2032
- battery cap
- handlebar bracket
- transmitter
- cable ties for mounting
- spoke magnet

1. Mounting

The handlebar bracket can be mounted on the handlebar and also on the stem.

Bild A: Mounting is possible on handlebar (Position A-1) or stem (Position A-2).
Bild B: For using it on the stem, change bracket mounting orientation from Position A to Position B.
Remove the protective tape.
Place the handle bar and fasten it with the cable ties.
Bild C: Mount the transmitter with cable ties on the fork (max. distance to the handlebar bracket max. 60 cm; best mounting on the right side, handlebar bracket and transmitter should be on the same side).
Bild D: Fix the magnet on a spoke so that it will face the mark on the transmitter. Adjust the magnet position and fine tune the sensor if necessary (distance between transmitter and magnet max. 3 mm).
Bild E: Rotate the CM 4.4A to 45 degree left and install it into the bracket. Then rotate it 45 degrees right to lock it. To unlock, rotate 45 degrees to the left.

1.1 Mounting of optional cadence-set
(separately available)
Mount the handlebar as described above on the handlebar or on the stem.
Place the sensor on the cable on the left chain-brace in height of the crank with help of cable-ties so that it is still loose enough to be lined up. Mount the cadence-magnet (with help of a cable tie) on the inside of the crank. The distance between magnet and sensor should be max. 3 mm.
The magnets must point directly to the mark on the sensor. Now switch on the cadence measuring in the setting mode of the CM 4.4A (see chap. 2.1). Turn crank a few times to check if the mounting is correct. Now tighten the cable-ties.

1.2 Putting on the heart rate transmission belt
Warning: whoever carries out sport should have a general medical check up on his/her general state of health - especially beginners, persons older than 35 years of age and anyone who has suffered from illnesses or injuries in the past. It is recommended that a doctor be consulted in any case in the presence of risk factors, such as smoking, high blood pressure, high cholesterol values, diabetes, lack of exercise and excess weight.

Pacemaker wearers should consult their doctor before using any heart rate measurement device!

The transmitter belt is hung in the elastic chest belt and fastened around the upper body. The transmitter (plastic part with the Ciclo-logo) should lie over the middle of the upper stomach, immediately below the breastbone, so that the logo on the transmitter is legible (viewed from the front) (see illustration). The electrodes in the belt, to the right and left of the transmitter, must be in contact with the skin. Pull the belt tight so that it cannot slip and constant contact with the body is guaranteed during movement.
If the CM 4.4A fails to display any heart rate, it probably means that there is no contact between the skin and the electrodes. Moistening the electrodes and the underlying skin often helps. Best results are obtained if electrode gel is used (available from pharmacies).
Measurement of the heart rate is only possible if the transmitter belt is fitted correctly and the CM 4.4A is within the transmitter's reception range (max. 60 cm).

2. Preparation

Inserting the battery
Insert battery type CR2032 with plus-pole facing up. Close battery cap with a coin, being sure not to over tighten. After inserting the battery the display will show normal mode.
(If nothing or incomprehensible signs appear in the display, press the AC-button on the rear of the computer with help of a ballpoint pen or a similar object. Attention: this will delete all values and setting).

2.1 Settings
Enter setting mode by pressing centre button for 3 seconds. Display shows 'SET BIKE1'.

To quit setting mode press again centre button for 3 seconds in any setting.
(To change the display to german language, press left button short, display shows ‚LANGUAGE'. Press centre button to choose this function and then switch between 'English' and 'Deutsch' with right button. To store press left button and then get back to setting mode with short pressing of right button).
Though CM 4.4A can show german and english words, this manual shows both possible displays.

The different setting modes can be shown by pressing right or left button, by pressing centre button the shown setting mode is chosen.

Possible setting modes:
SET ALT / SET HOEHE
SET BIKE1 / SET RAD1
SET CLOCK / SET UHR
SET HR / SET HF
SET MISC
EXIT / ENDE
LANGUAGE / SPRACHE

Each setting mode can have different setting possibilities.

The following is valid for these settings: the blinking value can be changed with the right button, the value is stored by shortly pressing the left button and the next value blinks or the next value appears on the display.

For a better reading in the following chapters the setting modes are **fat printed** and the settings **fat and italic**.

SET ALT / SET HOEHE
To define altimeter settings.
To select, press the centre button.

ALTITUDE / HOEHE
To change current altitude
Range: -300 to +6000m
Set with right and left buttons, continue with left button
Here you can change the altitude if displayed, e.g. if you notice that the current altitude diverges from altitude shown in the display (e.g. if barometric pressure changes).

G Tire size		Circumference
40-559	26 x 1,5	2026 mm
44-559	26 x 1,6	2051 mm
47-559	26 x 1,75	2070 mm
50-559	26 x 1,9	2026 mm
54-559	26 x 2,00	2089 mm
57-559	26 x 2,125	2114 mm
37-590	26 x 1 3/8	2114 mm
32-620	27 x 1 1/4	2199 mm
40-622	28 x 1,5	2224 mm
47-622	28 x 1,75	2268 mm
40-635	28 x 1 1/2	2265 mm
37-622	28 x 1 3/8	2205 mm
20-622	700 x 20C	2114 mm
23-622	700 x 23C	2133 mm
25-622	700 x 25C	2146 mm
28-622	700 x 28C	2149 mm
32-622	700 x 32C	2174 mm

HOME OFF / HEIM AUS
To switch the home altitude on/off
Default: OFF
Set with right button, continue with left button
Here you can switch the automatic reset off the home altitude value on/off

HOME ALT / HEIMHOEHE
Range: -300 to +6000m
Set with left or right button, continue with left button
CM 4.4A has got a barometric altimeter which adapts itself to temperature variations.
Changes of barometric pressure (e.g. during the night) can cause variations of the indicated altitude in the display. To compensate for these variations you can set the altitude of your origin (e.g. starting point such as home). With each reset of the daily range (deletion) the current altitude will be reset to the adjusted altitude.

UNIT m
Set unit of measurement for altitude
Default: m (meters)
Here you can select whether the indication is meter (m) or feet (ft).

UNIT °C
Set unit of measurement for temperature
Default: °Celsius
Here you can adjust whether the indication is Celsius (C) or Fahrenheit (F).

SET BIKE1 / SET RAD1
Set of bike-specific values, e.g. total distance, circumference, unit and more for bike 1.
Choose with centre button.
To do these settings for bike 2, press right and left button short simultaneously in normal mode. CM 4.4A switches to bike 2, then enter again setting mode (display then shows SET BIKE2/SET RAD2).

DAY DST / TAGES–DST
Set of the daily distance
Default: 000.00 km
Range: 000,00 to 999,99 km or m
Set with right and left button, store with left button.
Here the daily distance can be adjusted, e.g. the point of starting a tour, when using a printed tour-guide.
(This setting doesn't change the total distance. There only really ridden kilometres are counted).

TOT DST / GES. DST
Set of the total distance
Default: 0000 km
Range: 0 to 99999 km or m.
Set with right and left button, store with left button.
Here the total distance can be adjusted.

Wheel/Radumf.
Set of circumference
Default: 2080 mm
Range: 1000-3999 mm
Set with right and left button, store with left button.
Here the circumference can be adjusted.

The circumference of the wheel can be taken from the chart (Pict. G) or be measured by yourself.
Measuring the circumference of the wheel (for a more precise setting):
Put a marking at the front-tire and on the ground (e.g. with chalk). Ride straight ahead exactly one turn of a tire (for a very exact measurement, check the pressure of the tire before getting on your bike) and mark this position on the ground. Now measure the exact circumference of the wheel between the two markings at the ground (in mm) – see pict. 7.

Unit km bzw. Unit mi
Set of the measuring unit (kilometres or miles)
Default: km
Set with right button, store with left button
Here you can choose whether the display should show kilometres (km/h) or miles (m/h).

CAD OFF/TRITT AUS
Switch cadence on/off (ON/AN – OFF/AUS)
Default: OFF/AUS
Set with right button, store with left button
Here you can switch on/off the cadence measuring. To use this function you need the optional cadence-set (available at your local dealer).

SET CLOCK / SET UHR
Set of clock, date and clocktime-format.
Choose with centre button

Time / Uhrzeit
Set of clock
Range: 00:00 to 23:59 or 12:00 to 11:59 A/P
Set with right and left button, store with left button
Here you can set the current clocktime. First you set the hours, then the minutes.

Year / Jahr
Set of the year
Default: 2007
Range: 2007 to 2099
Set with right button, store with left button
Here you can set the current year.

Month / Monat
Set of the month
Default: 01
Range: 01 to 12
Set with right button, store with left button
Here you can set the current month.

Day / Tag
Set of the day
Default: 01
Range: 01 to 31
Set with right button, store with left button
Here you can set the current day.

Clock / Zeit
Set of the clock format
Default: 24
Set with right button, store with left button
Here you can select between 24- or 12-hour format (AM/PM).

SET HR / SET HF
Adjustments for the optional heart rate measurement. To use this function you need the optional heart rate-set (available at your local dealer).

HR OFF/ON / HF EIN/AUS
Switch heart rate on/off (ON/AN – OFF/AUS)
Default: OFF/AUS
Set with right button, store with left button
Here you can switch on/off the heart rate measuring.

Fitness / Fitness
Adjustment of the fitness level.
Default: 3
Set with right button, store with left button.
Range 1-4, corresponding to the following levels:
1 – poor fitness
2 – average fitness
3 – good fitness
4 – high fitness
Here you set your personal fitness level, necessary for the CICLOInZone®-calculation.

Sex / Geschlecht
Set with right button, store with left button.
Change between
m = male and f = female.
The sex is needed for the CICLOInZone®-calculation and the calorie consumption.

Weight / Gewicht
Range: 20 to 220 kg
Set with right and left button, store with left button
The weight is needed for the CICLOInZone®-calculation and the calorie consumption.

Birthdate /Gebjahr
Adjust with right and left button, store with left button
Default: 1960
Range: 1920 to 2006
The year of birth is necessary for the CICLOInZone®-calculation.

InZone
Here you can start the CICLOInZone®-calculation by short pressing of right and left button simultaneously (see also chap. 4 for CICLOInZone®).
In order to ignore the calculation, just press short left button.

In order to obtain an exact calculation of ones personal CICLOInZone® it is necessary to insert the personal data relative to fitness-level, sex, weight and birthdate.
In order to calculate the CICLOInZone® position the chest belt correctly, take up a rest position (remain seated and relaxed) and start the CICLOInZone® calculation by short pressing of right and left button simultaneously.
The CM 4.4A will then start to time 5 minutes. During this time, stay seated, relaxed and calm, as the CM 4.4A will measure the minimum heart rate reached during this period (heart rate at rest) and will store this value for the subsequent calculation.
After the 5 minutes the lower value of the calculated personal CICLOInZone® appears in the display.

Lower HR / untere HF
A lower heart rate limit can be set here or (after CICLOInZone-calculation) the calculated value is shown.
When the current heart rate is lower than this value, the CM 4.4A shows an arrow (▼) as an optical alarm.
Range: 0 to 220 bpm
Adjust with right and left button, store with left button

Upper HR / obere HF
An upper heart rate limit can be set here or (after CICLOInZone®-calculation) the calculated value is shown.
When the current heart rate is higher than this value, the CM 4.4A shows an arrow (▲) as an optical alarm.
Range: 0 to 240 bpm
Adjust with right and left button, store with left button

Max HR / Max HF
Shows the maximum heart rate, calculated with CICLOInZone®.
Range: 0 to 240 bpm
Adjust with right and left button, store with left button

SET MISC
Here you can switch on the powerdown-mode or make a reset (delete all values).
Choose with centre button

Powerdown/ STROMSPAR
Switch on the powerdown-mode (e.g. before changing of the battery, to save the values).
To switch it on, press right and left button short simultaneously, display fades out and CM 4.4A is in powerdown-mode. By short pressing of any button, CM 4.4A starts again and displays normal mode.

Reset / Löschen
Here you can delete all values (including the total values). For this press right and left button short simultaneously, display shows ‘reset' and then normal mode.

If you only want to delete the day values, press right and left button for three seconds in normal mode.

3. Functions

The CM 4.4A has an automatic start/stop when on the handlebar bracket.
That means, 4 sec. after the first wheel turn the display shows normal mode and the current speed.
1 minute after the last wheel turn (and without a button is pressed) the display changes to an "energy save" mode.
If the wheel turns or a button is pushed, the computer will resume normal functions.
CM 4.4A has got three modes: Bike 1, Bike 2, and Non-Bike mode.
To switch from one mode to another, simultaneously press the right and left buttons briefly (switching is only possible if speed = 0).
The centre display shows ① or ② depending on whether the selected mode is Bike 1 or Bike 2. The Non-Bike mode doesn't show any figures in the display. The Non-Bike mode can be used for tours without a bike (e.g. with a dedicated wristlet). It only shows values which have nothing to do with the bike movements.
The optional heart rate measuring works also without speed signal: when CM 4.4A is in normal mode (by pressing any button or auto-start), the heart rate receiver is automatically switched on.
And as long as a heart rate is shown in the display, there is no automatically switching to sleep mode.

To reset all day values, press right and left button for three seconds.

The CM 4.4A has a three-lined display. In the centre part the current speed is shown, with a small ① or ② beside, that shows whether the current values are valid for bike 1 or bike 2.
To advance the **functions** of the **upper display**, press **right button**, to advance the functions of the **lower display** press **left button**.
Always short pressing of the centre button shows the sub-functions of the function in the lower display.

Important for all sufunctions: display shows settings for 10 seconds befor switching back to main function.

Functions of upper display:
TM – Daily Ride Time (pict. 2)
DST – Daily distance (pict. 4)
Altitude (pict. 3)
HR (♥)
Time (pict. 1)

Function of centre display:
SPD – Current Speed
Inidcates the current speed in km/h or m/h .
Range: 0 to 199,9 km/h or m/h
An arrow on the left side of the display displays, whether the current speed is faster (arrow up) or slower (arrow down) than the current average speed.

Functions of lower display:
DST – Daily Distance (pict. 5)
Displays the distance ridden up to now in kilometres or miles..
Range: 0 to 999,99 km or mi

TOT – total distance (pict. 6)
Sub-function "Daily Distance"
Displays the total distance ridden up to now in kilometres or miles (since last reset or battery change).
Range: 0 to 99999 km or mi

∑TOT – sum of total distance of bike 1 and bike 2 (pict. 7)
Sub-function of "Daily Distance"
Displays the sum of the total distance ridden up to now in kilometres or miles (since last reset or battery change) of bike 1 and bike 2.
Range: 0 to 199999 km or mi

Current Altitude (pict. 18)
Displays the current altitude (above sea level). The altitude is displayed in intervals of 1 meter. It is determined by the barometric pressure. For this reason, the altitude value is dependent on weather variations.
Range: -300 to +6000 m or ft.

Attention! The altitude values will be added together from the signals received from the bike. In the Non-Bike mode they will be added together during the whole time.

Daily distance of altitude upwards (pict. 19)
Sub-function of "Current Altitude"
Displays the altitude travelled upwards.
Range: 0 to 20000 m or ft

Daily distance of altitude downwards (pict. 20)
Sub-function of "Current Altitude"
Displays the altitude travelled downwards.

MAX – maximum altitude (pict. 21)
Sub-function of "Current Altitude"
Displays maximum altitude of the tour.
Range: -300 to +6000 m or ft.

TOT – total of altitude upwards (pict. 22)
Sub-function of „Current Altitude"
Displays total distance of altitude upwards
Range: 0 to 20000 m or ft

TOT – total altitude downwards (pict. 23)
Sub-function of „Current Altitude"
Displays total distance of altitude downwards
Range: 0 to 20000 m or ft

∑TOT sum of altitudes from Bike 1 and Bike 2 (pict. 24)
(This function doesn't exist in No-Bike mode)
Sub-function of „Current Altitude"
Displays sum of altitude upwards.
Range: 0 to 20000 m or ft

Current ascent / descent (pict. 25)
Displays current ascent or descent as percentage. The symbol on the left side of the display shows whether it is ascent (▲) or descent (▼). Range: 0 to 100%

Attention: For technical reasons, the current percentage will only be shown after 50 - 100 m. This depends also on your speed.

Average ascent (pict. 26)
Sub-function of „Current ascent/descent"
Displays the average of the ascent values recorded so far.
Range: 0 to 100%

Average descent (pict. 27)
Sub-function of „Current ascent/descent"
Displays the average of the descent values recorded so far.
Range: 0 to 100%

Maximum Ascent (pict. 28)
Sub-function of „Current ascent/descent"
Displays the maximum of the ascent values recorded so far.
Range: 0 to 100%

Maximum Descent (pict. 29)
Sub-function of „Current ascent/descent"
Displays the maximum of the descent values recorded so far.
Range: 0 to 100%

Ø – Average Speed (pict. 8)
Displays the current average speed in km/h or mi/h.
Range: 0 to 199,9 km/h or m/h (the decimal place is highranking)

MAX – Maximum Speed (pict. 9)
Sub-function of "Average speed"
Displays the highest speed so far in km/h or mi/h.
Range: 0 to 199,9 km/h or m/h (the decimal place is highranking)

Temperature (pict. 30)
Displays current temperature
Range: -10 to +50 °C or °F

Attention: If you carry the CM 4.4A on your body, the measured temperature can vary from outside temperature.

MIN – Minimum Temperature (pict. 31)
Sub-function of „Temperature"
Displays minimum measured temperature.
Range: -10 to +50 °C or °F

MAX – Maximum Temperature (pict. 32)
Sub-function of „Temperature"
Displays maximum measured temperature.
Range: -10 to +50 °C or °F

Time (pict. 10)
Displays the current time.
Range: 00:00:00 to 23:59:59 or 12:00:00 to 11:59:59 AM/PM

Date (pict. 11)
Sub-function of "Time"
Displays the current date (dd.mm.yy).

TM – daily ride time (pict. 12)
Displays the current daily ride time.
Range: 0 to 9:59:59 h

TOT – total ride-time (pict. 13)
Sub-function "Daily Ride Time"
Displays the total ride time (since last reset or battery change).
Range: 0 to 999:59 h

∑TOT – sum of total ride time of bike 1 and bike 2 (pict. 14)
Sub-function of function daily ride time
Displays the sum of the total ride time (since last reset or battery change) of bike 1 and bike 2.
Range: 0 to 999:59 h

The following functions (heart rate and calorie consumption) only appear, if heart rate is switched on in the setting mode (for the measuring of heart rate you need the separately available heart rate-set).

HR - heart rate (pict. 36)
Indicates the current heart rate (bpm = beats per minute)
Range: 0 to 250 bpm
On the right side of the lower display an arrow shows, whether the current heart rate is below (▼), within (▼▲) or above (▲) the set heart rate limits.

Ø - average heart rate (pict. 37)
Sub-function of heart rate function
Indicates the average heart rate (since last reset).
Range: 0 to 240 bpm

MAX - maximum heart rate (pict. 38)
Sub-function of heart rate function
Indicates the maximum heart rate reached (since last reset).
Range: 0 to 240 bpm

Training time below the lower limit set for heart rate (pict. 39)
Sub-function of the heart rate measurement function.
Displays the training time during which heart rate dropped below the lower limit set.
(since last reset).
Range: 0 to 9:59:59 h

Training time within the limits set for heart rate (pict. 40)
Sub-function of the heart rate function.
Indicates the training time during which heart rate was within the limits set (since last reset).
Range: 0 to 9:59:59 h

Training time above the upper limit set for heart rate (pict. 41)
Sub-function of the heart rate function.
Indicates the training time during which heart rate exceeded the upper limit set (since last reset).
Range: 0 to 9:59:59 h

kCal - Calorie consumption (pict. 42)
Indicates the current calorie consumption (since last reset).
Range: 0 to 99999 kCal

TOT - total calorie consumption (pict. 43)
Sub-function of calorie consumption function
Indicates the total calorie consumption (since last reset or battery change)
Range: 0 to 99999 kCal

The following function only appears, if switched on in the setting mode (for the measuring of the cadence you need the separately available cadence set).

CAD - cadence (pict. 33)
Indicates the current cadence (rpm = rounds per minute)
Range: 0 to 250 rpm

Ø - average cadence (pict. 34)
Sub-function of function cadence
Indicates the average cadence.
Range: 0 to 250 rpm

MAX - maximum cadence (pict. 35)
Sub-function of function cadence
Indicates the maximum reached cadence.
Range: 0 to 250 rpm

4. CICLOInZone®-Philosophy and use

CICLOInZone® is a solution for the very best personalisation of your training routine.

It is possible to calculate the optimum training threshold with the CICLOInZone® function on the basis of your personal data and your pulse rate when at rest.

CICLOInZone® is the ideal solution for personalised cardio training applied to any sport, from jogging and cross-country running to road and indoor cycling.

Improve your fitness? – Lose weight? – Train whilst always taking your health into consideration? Everyone will find the correct aim to follow in their training. But how do you train to achieve those aims in the most efficient possible manner? How do you find the right intensity of effort during the training? CICLOInZone® is the optimum training ZONE for effort, resistance and weight loss.

What does CICLOInZone® do?
It calculates the optimum training zone for effort, resistance and weight loss.

The values vary from person to person and they offer a valid training support – always staying between 70 % and 85 % of the maximum heart rate.

(+/- 5% of tolerance, taking into consideration the actual heart rate when at rest and the level of training).
The question of burning fat is seen in the "correct" light with CICLOInZone® – on the basis of the personal data collected.

5 . Battery change

CM 4.4A: Open battery cap with a coin (unscrew to the left). Insert battery type CR2032 (please use battery with smooth minus-pole) with plus-pole facing up. Close battery cap, being sure not to over tighten. After inserting the battery the display will show normal mode.

If nothing or incomprehensible signs appear in the display, press the AC-button on the rear of the computer with help of a ballpoint pen or a similar object. Attention: this will delete all values and setting.
(Battery change in the optional chest belt works in the same way.)

Transmitter: Open battery cap at the top of the transmitter with a coin (unscrew to the left), remove old battery and insert new 12 V battery, type 23A (with pluspole facing up). Close battery cap, being sure not to over tighten.

Please do not throw away battery in your normal garbage.

6. Trouble shooting

Faulty or no display
- check to see if battery is installed properly or replace battery (Attention: removing battery will clear all settings and values in the CM 4.4A)
- press AC-button on the rear of the computer

Speed not displayed
- check to see if wheel-sensor is mounted properly
- check the position of the spoke magnet (max. 3 mm distance to wheel-sensor)
- make sure CM 4.4A is mounted in bracket correctly
- check wheel circumference

Speed to high or to low
- check wheel circumference
- check to see if you are using miles or kilometers

Incorrect display of altitude:
- Check the home altitude (basic settings). Perhaps the settings were made incorrectly.
- Changing barometric pressure as a result of changing weather (readjust current altitude)

No heart rate displayed or values displayed are incorrect or unstable
- proof whether heart rate is switched on in setting mode
- Check transmitter belt (battery)
- Skin too dry or cold
- Distance between CM 4.4A and transmitter belt is too great (max. 60 cm)

Cadence is not displayed or value incorrect or unstable
- Check whether switched on in setting mode
- Check sensor and magnet for correct installation

7. Guarantee

We offer a guarantee for 24 months from the date of purchase on the CM 4.4A. The guarantee is limited to material and processing faults. The batteries are excluded from the guarantee.

The guarantee is valid only if the computer, with accessories, has been handled and maintained carefully and according to operating instructions.

To return the CM 4.4A under conditions/terms of the guarantee, please refer to your dealer, your local distributor or send the computer with the proof of purchase (date) and all accessories and with sufficient postage, to:

CicloSport Service
K. W. Hochschorner GmbH
Einsteinstr. 39a
D-82152 Martinsried

ciclo-service@ciclosport.de
www.ciclosport.de

Please read through the instruction manual carefully before sending us your computer and check the battery. An exchange-device or the repaired device will sent back to you free of charge if justifiable guarantee-claims have come into question. Please contact our local distributor.

Repair: If your CM 4.4A is sent in for repair (or battery change) or if a guarantee claim is not valid, repairs up to EUR 19.- will be carried out automatically. In case of higher repair costs you will be notified. The repaired device will be sent back COD.

Disposal of Old Electrical & Electronic Equipment (Applicable in the European Union and other European countries with separate collection systems)
This symbol on the product or on its packaging indicates that this product shall not be treated as household waste. Instead it shall be handed over to the applicable collection point for the recycling of electrical and electronic equipment. By ensuring this product is disposed of correctly, you will help prevent potential negative consequences for the environment and human health, which could otherwise be caused by inappropriate waste handling of this product. The recycling of materials will help to conserve natural resources. For more detailed information about recycling of this product, please contact your local city office, your household waste disposal service or the shop where you purchased the product.

1 18:52 / 35² / 0°Km/h	**2** 1:38:10 / 35² / 0°Km/h	**3** 2250 / 35² / 0°Km/h	**4** 199.53 / 35² / 0°Km/h	**5** 10² / 999.99 Km	**6** 10² / TOT 99999	**7** 10² / ∑TOT199999	**8** 10² / 199°Km/h
9 195959 / 10² / MAX 199⁹	**10** 195959 / 10² / 12:59:59PM	**11** 195959 / 10² / 12.04.2006	**12** 195959 / 10² / TM23:59:59	**14** 195959 / 10² / TOT999:59	**15** 195959 / 10² / 350 rpm	**16** 195959 / 10² / 100	
17 195959 / 10² / MAX 250	**18** 195959 / 10² / 350 m	**19** 195959 / 10² / 1300↑	**20** 195959 / 10² / 1250↓	**21** 195959 / 10² / MAX 2380	**22** 195959 / 10² / TOT 7300↑	**23** 195959 / 10² / TOT 7000↓	**24** 195959 / 10² / ∑TOT183501
25 195959 / 10² / 7%	**26** 195959 / 10² / 6%	**27** 195959 / 10² / 7%	**28** 195959 / 10² / MAX 15%	**29** 195959 / 10² / MAX 14%	**30** 195959 / 10² / 26°C	**31** 195959 / 10² / MIN -5°C	**32** 195959 / 10² / MAX 10°C
33 195959 / 10² / 250 rpm	**34** 195959 / 10² / 100	**35** 195959 / 10² / MAX 250	**36** 195959 / 10² / 250 HR	**37** 195959 / 10² / 100	**38** 195959 / 10² / MAX 250	**39** 195959 / 10² / 23:59:59↓	**40** 195959 / 10² / 23:59:59↑
41 195959 / 10² / 23:59:59↑	**42** 195959 / 10² / 99999KCAL	**43** 195959 / 10² / TOT 99999					